

## Z-Select™ 2000D 190 Tag

<b>Media Type</b>	Label		<b>Adhesive Type</b>	Permanent	
	Receipt			Removable	
	Tag	✓		No Adhesive	✓
	Wristband			<b>Environment</b>	Indoor
<b>Material Type</b>	Paper	✓	Outdoor		
	Synthetic		<b>Properties</b>	Cold Temperature	
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)	✓		Deep Freeze	
	Thermal Transfer (Ribbon Required)			High Temperature	
<b>Finish</b>	Matte	✓		Ultra High Temperature	
	Gloss			High Tack	
				Chemical Resistance	-

Note: Z-Select™ 2000D 190 Tag is not recommended for applications involving long term exposure to sunlight, extreme heat or applications involving extended exposure to moisture or solvents.

### Z-Select materials feature a protective topcoat, which provides the following benefits over an equivalent uncoated material (e.g. Z-Perform)

- Excellent print quality and definition
- Faster print speeds
- Improved printhead life

### Additional Features

- No ribbon required for direct thermal printing, therefore only one stock item needed
- Improved resistance to image fading under direct sunlight or UV light compared to the Z-Perform™ 1000D tag products
- BPA free

### Suggested Applications

- Shelf-edge tags
- Visitor identification tags
- Admission tickets
- Inventory control and shop floor tracking
- Transportation tickets
- Packaging inserts / work in progress tags

## Technical Specifications

	Description	Caliper
<b>Facestock</b>	180gsm matte white topcoated thermal imaging paper tag	190 microns
	<b>Total</b>	<b>190 microns ±10%</b>

**Recommended Zebra Printers:**

Desktop, mid-range and high-performance thermal printers

**Minimum Application Temperature:**

When the label is applied, the environment and surface should be above this temperature

N/A

**Service Temperature Range:**

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

-5°C to 49°C

**Recommended Storage Conditions:**

Storage of product before use

6 months duration when stored at 20°C to 24°C at 50% RH

**Expected Life Span in Application:**

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

Indoor use, up to 1 year

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, order from the ZipShip price list or order sample roll SAMPLE5222.